

# Specifications

imagePROGRAF iPF5000



## Printer

<b>Printer Type</b>	Print Head: PF-01 Technology: FINE (Full-lithography inkjet Nozzle Engineering) Configuration: <ul style="list-style-type: none"><li>• 6 colors per print head</li><li>• Dual print heads (total 12 colors)</li><li>• Print Head (A) Y/PC/C/PGY/GY/MBK</li><li>• Print Head (B) PM/M/BK/R/G/B</li></ul>
	Replacement: End user replaceable
<b>Number of Nozzles</b>	Nozzle Text: 2,560 nozzles per color 30,720 nozzles total
<b>Nozzle Pitch</b>	1,200 dpi
<b>Nozzle Recovery System</b>	Non-firing nozzle detection and compensation
<b>Print Resolution (up to)</b>	2,400 x 1,200 dpi (Max)
<b>OS Compatibility</b>	Windows® 98SE/ME/2000/XP/2003 Server, Macintosh® OS 9.1/X 10.2/10.3/10.4 <sup>1</sup>
<b>Standard Interface</b>	USB 2.0 High-Speed 10/100 Base-T/TX Optional: IEEE 1394 (Firewire®)
<b>Ink Droplet Size</b>	4 picoliter
<b>Ink Capacity</b>	130ml per color <sup>2</sup>
<b>Ink Types</b>	Ink Type: Lucia ink (Pigment-based)
<b>Buffer/Ram</b>	192 MB
<b>Media Width</b>	8"-17" (Cut sheet and roll)
<b>Media Thickness</b>	Cassette: 0.83-0.3 mm (3.2-11.8 mil) Top Loading Manual Feed: 0.08-0.5 mm (3.2-19.6 mil) Front Loading Manual Feed: 0.5-1.5 mm (19.6-59.0 mil) Roll: 0.07-0.8mm (2.8-31.4 mil)
<b>Maximum Roll Print Length</b>	59 Feet (18 meters) <sup>3</sup>
<b>Maximum Media Roll Diameter</b>	5.9" (150mm)
<b>Borderless Printing Width (Roll Media Only)</b>	10", 13", 14", 16", 17", B4 (10.12"/257mm),A2 (16.54"/420mm)
<b>Paper-Feed Method</b>	Cassette: Up to 250 sheets(Plain Paper, Letter), front output Top Loading Manual Feed: One sheet, front output Front Loading Manual Feed: One sheet, front output Roll Feed(Optional): One roll, front output

<b>Languages</b>	Language: GARO (Canon Proprietary)
<b>Noise Level (Approx.)</b>	Operation: 49 dB or less Standby: 30 dB or less
<b>Physical Dimensions</b>	39.3" x 28.9" x 12.5" w/ optional Roll Feed Unit: 39.3" x 31.9" x 13.5"
<b>Weight</b>	Approximately 99 lbs. w/ optional Roll Feed Unit: Approx. 108 lbs.
<b>Power Source</b>	AC-100-120V (50-60Hz)
<b>Power Consumption</b>	Maximum: 100W or less Standby 6W or less Power Off: Less than 1W (Compliant with Executive Order)
<b>Operating Environment</b>	Temperature: 59°-86° F (15°-30° C) Relative Humidity: 10-80% (No Condensation)
<b>User-replaceable items</b>	Item: Print Head (PF-01), Maintenance Cartridge (MC-05)
<b>Software Included</b>	Printing Software: Printer Driver 2006, Print Plug-in for Photoshop® <sup>4</sup> , Print Plug-in for DPP <sup>5</sup> , Printer Driver Extra Kit <sup>6</sup> (Free Layout, imageRUNNER Linking Function)  Applications: PosterArtist 2006 <sup>7</sup> , Digital Photo Print Pro <sup>9</sup>  Utilities: GARO Status Monitor, Media Configuration Tool, RemoteUI

#### Accessories

<b>Optional Accessories</b>	Auto Roll Feed Unit (RU-01) IEEE 1394 Expansion Board (EB-05)
-----------------------------	--

**The imagePROGRAF 5000 has not been authorized as required by the rules of the Federal Communications Commission. This Product is not, and may not be, offered for sale or lease, or sold or leased, until such authorization is obtained.**

<sup>1</sup>For imagePROGRAF Printer Driver 2006. For printing from PostScript applications such as Adobe Illustrator® or QuarkXPress®, please use a PostScript compatible RIP package. For a list of Canon recommended RIP packages, please consult with Canon Alliance and Industry Market program list of RIP vendors.

<sup>2</sup>The starter ink tanks that initially packaged with the printer have enough ink to fill the ink system, and are not the same capacity as the replacement ink tanks specified here.

<sup>3</sup>The maximum printable length varies depending on the application, OS, and RIP used. The maximum printable length from Printer Driver 2006 is 50 feet.

<sup>4</sup>For Adobe® Photoshop® 6, 7, CS, CS2, running on Windows 2000/XP or Macintosh OS 9.1 or OS X 10.2/10.3/10.4

<sup>5</sup>For Digital Photo Professional version 2.1 or later running on Windows 2000/XP or Macintosh OS X 10.2/10.3/10.4

<sup>6</sup>Windows 2000/XP/2003 Server

<sup>7</sup>Windows 2000/XP